

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant	:	Van L. Phillips et al.) Group Art Unit: 3738
Appl. No.	:	09/586,666)
Filed	:	June 1, 2000)
For	:	UNIVERSAL PROSTHESIS WITH CUSHIONED ANKLE))
Examiner	:	Bruce E. Snow))
)

DECLARATION OF PRIOR INVENTORSHIP UNDER 37 C.F.R. §1.131

United States Patent and Trademark Office P.O. Box 2327 Arlington, VA 22202

RECEIVED

SEP 1 7 2002

Dear Sir:

TECHNOLOGY CENTER R3700

I declare that:

- 1. I am an inventor of subject matter currently being claimed in the above-identified patent application.
- 2. Claims 1, 2, 4-8 and 11-47 of the above-identified application were rejected in an Office Action dated March 7, 2002. The rejection was based on Footnotes, Flex-Foot Brochure (Summer 1999) and K2 SensationTM, Flex-Foot Brochure (June 1, 1999).
- 3. I hereby declare that prior to Summer 1999 and June 1, 1999, the invention of each of the claims rejected in the March 7, 2002 Office Action was reduced to practice. For example, true and correct photocopies of technical illustrations and sketches of features of the claimed invention are attached hereto as Appendix A and were created prior to Summer 1999 and June 1, 1999. The dates have been redacted on the material of Appendix A.
- 4. I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these

Appl. No.

09/586,666

Filed

June 1, 2000

statements were made with the knowledge that willful, false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful, false statements may jeopardize the validity of the application or document, or any registration resulting therefrom.

Dated: Sept 5, 2002

By:

Hilary D. Pouchak

H:\DOCS\KOR\KOR-3069.DOC:kr 090402

FLEXFT.182A PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE Applicant: Van L. Phillips et al. Appl. No.: 09/586,666 Filed: June 1, 2000 For: UNIVERSAL PROSTHESIS WITH CUSHIONED ANKLE

Bruce E. Snow


APPENDIX A


Technical Illustrations and Sketches of the Claimed Invention Created Prior to Summer 1999 and June 1, 1999


RECEIVED
SEP 1 7 2002
TECHNOLOGY CENTER R3700


H:\DOCS\KOR\KOR-3066.DOC:KR 090302

Examiner









UNLESS OTHERWISE SPECIFIED PRODUCT: BELTING, POLYURETHANE IMPREGNATED **PECHICATIONS** OLOR: OFF-WHITE THICKNESS: .06" TENSILE STRENGTH: 780 LB/IN TENSILE FORCE FOR 1% ELONGATION: 68 LB/IN A WAS DWG# 60035. REV. A PER DCO# 99-341

ALIFORNIA INDUSTRIAL RUBBER CO. 339 SO. CHERRY AVE. RESNO. CA. 93706

SUPPLIER PART NUMBER: FN1-12E


P/N: CM162014

SPECIFICATION CONTROL DRAWING

DO NOT SCALE CRAINING	3		E NOTES	.111 ± .010 .11 ± .25°	. 1/10" . 3 ± .1	OVERWICE WIT: OVERWICE WIT: OVERWICE WIT:
HODEL NAME	THE PARTY OF THE P	CHORNE	BOSHA	\ 5	S. DAVIS	APPROVALS
CHICACHT 1 OF 1	B CMISSONA A	Ţ	REI TING TOE SUBELEI EY III	000 III.E	Flex-Foot Inc. Fax: (949) 362-3883	2742A Lagura His D: Also Vieja CA 22859

SEE NOTES

1/10" .1 ±



1.

•												•	٠			
ŧ	76740420	встотася	K2X40328	2404040	ze ro rec	92E07X2X	K2X40226	47C04V3V	TCEUTACA	4770477v	יכנתושני	7CLU7XCX	K2X40222	7710477	CC+O1YCA	₽
	[3	28	à	2 3	×	26	:	2	44	: :	2	22	1	3	SIZE
	2.50	2	3.50	3.6	¥ .	ž	3.25	٤	2	3.00	3 8	<u></u>	2.75	:	3	>
	1	2	3.75	200	3 8	Š	3.50	5	20	3.25	1 2	<u>, , , , , , , , , , , , , , , , , , , </u>	w 8	9	3	8
	25.5	3	13.5°	ت د	٤	200	13 O°	ō	,	16.0	ē	2	ъ. О°	ē		-
	9.50	;	9.50	8. 7	9.	2	8.75	è	;	7.00	:	3	5.75	2.7		2
	9	?	9.50	8.75	9.73	2	8.75).g		7.00	9	;	5,75	3.5		8
	Ö		:23	.25	İ	3	:25	ij	•	79	1	;	3	ij		2
•	35		.95	.88	ä	3	88	.82		.82	ä	3	:	.75		-
	8.25		8.25	7.63	1.01	;	7.63	7.00		7.00	è.		6.50	6.50	1.	-
·	6.77		6.77	6.25	0.25		6.25	5.75		5.75	5.75		5.25	5.25	7	~
	9.60		9.60	8.85	8.65		8.85	8.06		8.06	8.06		7.27	7.27	(3
	4.398		46£ 7	4.000	4.000		4.000	3.640	3.640		3.640		3.250	3.250	-	2
	1.981		981	1.860	1.860		1.860	1.650		1.650	1.650		267 1	1.423	٥	•
	1.50	1	5	1.26	1.26	_	1.26	1.10	L	. <u>.</u>	1. 10		70	.94	-	-
	2.600	8	2 600	2.417	2.417		2 47	2.250		2.250	2.250	200.2	2 092	2.082	(3	
	2.60	5	3	2.75	2.75	1	3 7	2.70		2.70	2.70	9:	3 6	2.60	>	•
	 8	ē	3	.g.	.93	٤	8	.8 		86	86	1	3	.79	-	
	.122	5	!	179	.098	į		.095		080	.066	è	3	.064	(
	.14.8	1.7	3	.145	.124	į	3	23		106	.092	Ė	3	.089	~	
	.237	2.2		.231	.210	3	2	.204]	180	.175	ē	;	.169	ت	
	.296	7		.289	.268	į		.261	1	346	.232	ž		.224	=	
	.30E	282		.298	.277	707		.270	į	ž	.241	147		.233	15	
	.292	.271		.285	.264	.249		.257	2.00	27.5	.228	235		.221	76	
	.278	.257		.271	.250	235		.243	077.	33.0	.214	.221		.207	17	
	.238	.217		.232	.211	196		205	.170	3	.176	.184		.170	18	
	211	.190		206	85	.170		.180		•	.151	.160		.146.	19	
	.779	.158		3	.15t	.139		.150	9	;	.121	.131	\int	.ij	710] .
	.56	.14.6		S	.11.	.129		5	5		. 111	.121	ŀ	107	a	


		r÷	i		· ·		1.	<u></u>	·	
K2X40427	K2X40327	K2X40425	K2X40325	К2Х40225	K2X40323	K2X40223	K2X40123	K2X40221	K2X40121	P/N
27	27	25	25	25	23	23	23	21	21	SIZE
K2X40428	K2X40328	K2X40426	К2Х40326	К2Х40226	К2Х40324	K2X40224	K2X40124	К2Х40222	K2X40122	TRIM DOWN FROM P/N

	₩.	
1:1 DES PLEIME KOYLOAAA DOW SHEET	9 6	>
VYXCX	K2X4	E, B
AAA NDL	ЮАА	воттом,
J		K 2
2		

	Ē	
	1:1	
į		
	1:1 DIE FLEIME KZX40AAA.ORW SIEET	
	(40AAA	
	.DRW	ľ
		1
l	~ 유	ŀ
	T 1	ŀ
L	_	_

ı		
i	8	
I	P. David	
ĺ	CX40AAA.DRW	
l	₹	
	SET.	
l	~	ļ
ı	윾	
l	•	


K2X40AAA 3 A PLATE, BOTTOM, K2 K2X40AAA





	T	T	1	T
K2X40004	K2X40003	K2X40002	K2X40001	P/N:
27-28 2.75	25-26	23-24 2.60	21-22	SIZE
2.75	2.68		2.55	A
1.97	1.80	1.70	1.53 .300	В
.340	.340	.300	.300	C
.72	.67	.63	.61	0
1.027 4.720	.997	.960	.950	
4.720	4.480	4.300	080.4	F
1.90	1.76	1.64	1.50	Ξ
1.40	1.30	1.20	1.10	-
2.75	2.68	2.60	2.55	*

B K2X400AA

REAL 1:1 DOG PLENAME K2X400AA.DRW DEET CONNECTOR, PLATE, TOP, K2







NOTES: UNLESS OTHERWISE SPECIFIED

1. INCOMING INSPECTION CRITERIA: INSPECT TO NOTED OVAL DIMS 2. FOAM BLOCK TO BE MARKED WITH MANUF. ID#.

WAS DWG# 60025; REV. C PER DCO# 99-347

TOP AND BOTTOM SURFACES SHALL HAVE MOLDED SKIN SKIVED OFF TO THICKNESS. SKIN IS ALLOWED ON ALL SIDE SURFACES.

SUPPLIER IS TO PROVIDE CERTIFICATE OF CONFORMANCE WHICH CONSISTS OF INSPECTION DATA.

PRODUCT: PURCELL CELLULAR VULKOLLAN POLYURETHANE

MANUFACTURER: PLEIGER PLASTICS COMPANY
WASHINGTON, PA PH: 800-753-4437

DESCRIPTION: NDI/POLYESTER BASED POLYURETHANE FOAM.
HIGH LOAD CAPACITY, ABRASION AND TEAR RESISTANT.
HIGH ELASTICITY WITH LOW PERMANENT DEFORMATION.

BLOCK SIZE:

THICKNESS - 55 mm (+3 mm/-2mm) WIDTH - 250 mm (+/-5 mm) LENGTH - 500 mm (+10 mm/-3 mm) OR 750 mm (+10 mm/-3 mm)


				:	•									
	. LM163079	20,00	6 M16 3078	[CM103077	CHANGE	92029UMJ	C11107070	CMICACOT		N/N		₽		
	15-60	נייני	33 24	15-50	10-40	15 7.7	0.4-C	10	כניינו	À		MANIFICATION		•
SOLV TITO ONNI I	3829-116 GDAMS	3497-3700 UKAMS	בייופה מפר מסיר	3169-3431 GRAMS	2017-30/3 UKAMS	מאותם כדמר מנפכ	2509-2716 URAMS	0500 0544 0544	21/9-2338 UKAMS	מינים מינים	MIN OOC × OC2 × CC	CC V SEO V EOO WY	BLOCK	
J/44-02 10 UKANS	SAVUS 81CF 11CS	5249-5682 GRAMS	THE CANALIS	1751-511.6 GDAMS	4259-4610 GRAMS	1000	3764-4073 GRAMS		1269-3537 GRAMS		55 X 250 X 750 MM	OPTIONAL	BLOCK SIZE	VEIGHT)
201-003		509-551	44 b-10 b	121 100	113-447	200	201-595		17. T.	(r 111/1/11)	(Ko (mo 4)	DENSITY		
a.00	3	7.50	0.50	,	5.50	5.50	, so	4.00	<u>~</u> 8	(7 mm/m)	לאם (אם ישהים) לבונטיו ובונטיונב	SILSNAT		
4/0		465	400	,	630	ā	210	0,00	200	(70)	רבטאטא ו וטא	FIGNERATION	FOR REFERENC	
20		18	14		12		\$	C	0	(KN/m)	ICAR	15.65	m	
.70	į	70	70		70	ď	3	2	7,	8	KCBUUNU	2000	ONLY	
55-54	2	05-07	35-45		07-08	25-35	3	20-30	3	SHORE A	HAKUNCSS			


SPECIFICATION CONTROL DRAWING


SEE ABOVE

SEE ABOVE

DO NOT SCALE DRAWING







1. Pacsus